

# Vinyl Outdoor Clear Sticker Stock.

**Product**

V302CG1

**Brand**

Hexis

**Website**[www.hexis-graphics.com](http://www.hexis-graphics.com)**Product Description**

A printable, 80µm calendered monomeric PVC film with a glossy, transparent finish and pressure-sensitive acrylic adhesive. Designed for digital printing with solvent, eco-solvent, latex, and UV inkjet printers.

**Features**

- Glossy, transparent finish for clear graphics and overlays.
- Compatible with multiple ink types (solvent, eco-solvent, latex, UV).
- Immediate, permanent adhesion; not repositionable.
- Good chemical resistance (alcohol, diluted acids, oils).
- Stable, easy-release liner: Silicone-coated PE paper for reliable processing.

**Applications**

- Print media for:
  - Glass, steel, aluminium, PVC, melamine, and other flat, smooth surfaces.
- Wet application possible.
- Suitable for both indoor and outdoor signage (vertical exposure).

**Not Recommended For**

- Textured or unclean surfaces.
- Surfaces with damaged or non-original paint.
- Substrates requiring repositioning during installation.

**Technical Specifications**

Film Thickness	80µm
Total Thickness	255µm
Total Weight	265g/m <sup>2</sup>
Liner	Silicone-coated PE paper, 145g/m <sup>2</sup>
Adhesive Type	Solvent-based acrylic
Shrinkage	<0.8mm (168h at 70°C)
Application Temp (min)	+10°C (+50°F)
Service Temp	-40°C to +90°C (-40°F to +194°F)
Elongation at Break	min. 100%
Shrinkage	<0.8mm (168h at 70°C)
Durability (vertical outdoor)	3 years (unprinted, flat surfaces)
Storage	1 year (15°C-25°C, 50% RH, unopened, dust-free, upright)