

# Vinyl Outdoor Sticker Stock.

**Product**

V240WG1 / V240WM1 – Polymeric PVC Film

**Brand**

Hexis

**Website**

[www.hexis-graphics.com](http://www.hexis-graphics.com)

**Product Description**

Printable film made of 70 µm calendered PVC with polymeric plasticisers. Designed for indoor/outdoor flat-surface applications. Glossy (WG1) or Matte (WM1) finish. Compatible with Solvent, Eco-Solvent, UV, and Latex inks.

**Features**

- Medium-term outdoor performance
- Immediate and permanent adhesion
- Surface laminates available for enhanced durability

**Applications**

- Flat surfaces: glass, steel, aluminium, PVC, melamine
- Not suitable for grainy or acrylic-painted surfaces
- Best on original, undamaged paintwork

**Technical Specifications**

Film Thickness	70 µm
Total Thickness	230 µm
Total Weight	260 g/m <sup>2</sup>
Liner	145 g/m <sup>2</sup> silicone PE, light grey print
Adhesive Type	Grey solvent acrylic, permanent
Initial Tack	15 N/25 mm (HEXFTM009)
Peel Strength (20 min)	17 N/25 mm (HEXFTM001)
Peel Strength (24 hr)	20 N/25 mm (HEXFTM001)
Release	0.2 N/25 mm (HEXFTM003)
Tensile Strength	≥ 35 N/25 mm
Elongation at Break	≥ 100%
Shrinkage	(168h @ 70°C) < 0.5 mm
Application Temp	≥ 10°C
Service Temp	Range -40°C to 90°C
Shelf Life	1 year at 15–25°C, 30–70% RH
Durability	(Vertical Outdoor) Unprinted: 5 yrs, Printed: 2 yrs, Printed + Laminate (V740): 3 yrs, VCR740: 2.5 yrs